



Influence of queue propagation and dissipation on route travel times

Raovic, Nevena

Publication date:
2013

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Raovic, N. (2013). *Influence of queue propagation and dissipation on route travel times*. Abstract from Strategisk forskning i transport og infrastruktur, Kongens Lyngby, Denmark.
http://wwwx.dtu.dk/Sites/strategisk_transportforskning2013/Program.aspx

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

IRUC

Influence of queue propagation and dissipation on route travel times

Nevena Raovic

DTU Transport

The representation of queue spillbacks in a congested network plays an important role in transportation network analysis. Dynamic network loading (DNL) models that are able to represent queue spillbacks suggest two approaches to represent traffic flow propagation. One is based on the kinematic wave theory (KWT) and it is used in the cell transmission model (CTM) and the link transmission model (LTM). The other represents the dynamic queuing models (DQM) which are used in the state-of-the-art dynamic traffic assignment (DTA) models and it is based on the idea of link representation through a queuing and a moving part. These characteristics enable both models to represent queues and their spillbacks, but also introduce a significant difference between them. Firstly, the KWT relies on the first-in-first-out (FIFO) rule, which means that models such as the CTM and LTM cannot take multiple vehicle classes into account (Bliemer, 2008). Yperman (2007) indicates that there is a significant difference in queue-propagation and queue-dissipation between the LTM and DQM. This results in different route travel times, and can further affect route choice. In this paper, different approaches to represent queue propagation and dissipation through the CTM, LTM and DQM are studied. A simple network allows to show how these approaches influence route travel time. Furthermore, the possibility of changing the existing DQM is considered in order to more realistically represent queue propagation and dissipation, which would lead to more accurate route travel times.